Verifying configurations was the easy part

My ongoing quest toward correct network operations

Formally Verified



Laurent Vanbever


nsg.ethz.ch | netfabric.ai

FMANO

Mon Sept 8 2025







Home > My Europe > Europe News > Flight delays after technical glitch closes Swiss airspace

M.europe Europe NEWS

Flight delays after technical glitch closes Swiss airspace




By **Euronews** with **AFP** • Updated: 15/06/2022



This network outage lasted ~2 hours


This network outage lasted ~2 hours

caused by a hardware failure



Gone in Minutes, Out for Hours: Outage Shakes Facebook

When apps used by billions of people worldwide blinked out, lives were disrupted, businesses were cut off from customers — and some Facebook employees were locked out of their offices.





This network outage lasted ~7 hours

This network outage lasted ~7 hours

caused by a misconfiguration

Networks are ...

Networks are easy to break

Networks are easy to break hard to repair

Networks are **easy** to break **hard** to repair

How come?

Configuring networks is hard because of a fundamental semantic gap

distributed algorithms


distributed algorithms


per-device forwarding state


outputs

network operators









Human factors contribute to between 65% and 80% of all downtime incidents

Network verification promises to significantly increase network reliability

Network verification promises to significantly increase network reliability

What is it?

Network verification

Given specification φ



Network verification

Given specification φ and configuration $\mathcal C$

Network verification

Network verification has been wildly successful

Network verification has been wildly successful, academically

Debugging the Data Plane with Anteater University of Illinois at Urbana-Champaign {mai4, khurshi1, agarwa16, caesar, pbg, kingst}@illinois.edu ABSTRACT 1. INTRODUCTION

Categories and Subject Descriptors

General Terms

Today's networks typically carry or deploy dozen of protocols and mechanisms simultaneously such as MPLS, NAT, ACLs and route redistribution. Even when individual protocols further correctly, failures can arise from the complex interactions of their aggregate, requiring network administrators to be masters of detail. Our goal is to automatically find an important class of failures, regardless of the protocols running, for both operational and experimental networks.

Peyman Kazemian

Header Space Analysis: Static Checking For Networks

varghese@cs.ucsd.edu

agnostic framework, called Header Space Analysis (HSA). Our formalism allows us to statically check network specifications and configurations to identify an important class of failures such as Reachability Failures, Forwarding Loops and Traffic Isolation and Leakage problems. In HSA, protocol header fields are not first class entities; instead we look at the entire nacket header class entities; instead we look at the entire packet header as a concatenation of bits without any associated mean. Each packet is a point in the $\{0,1\}^k$ space where L is the maximum length of a packet header, and networking boxes transform packets from one point in the space to another point or set of points (multicast). Thus, our first goal is to help system administrators L to the packets of the packets L to the space of the packets L to the packets

Nick McKeown

ing boxes transform packets from one point in the space to another point or set of points (multicast).

We created a library of tools, called Hassel, to implement our framework, and used it to analyze a variety of retworks and protocols. Hassel was used to analyze the Stanford University backbone network, and found all the forwarding loops in less than 10 minutes, and verified reachability constraints between two subnets in 13 seconds. It also found a large and complex loop in an experimental loose source routing protocol in 4 minutes.

fic in one slice (e.g. a VLAN) cannot leak into another in the beginning, a switch of router was breatinast in information about a patient can be read by other ingly simple. About all the device needed to do was index into a forwarding table using a destination address, and decide where to send the packet next. Over time, forwarding grew more complicated. Middleboxes (e.g., NAT and firewalls) and encapsulation mechanisms (e.g., NAT and firewalls) and encapsulation mechanisms (e.g., NAT bypasses address limits and MPLS appeared to escape from IP's limitations: e.g., NAT bypasses address limits and MPLS VeriFlow: Verifying Network-Wide Invariants in Real Time

Ahmed Khurshid, Wenxuan Zhou, Matthew Caesar, P. Brighten Godfrey Department of Computer Science University of Illinois at Urbana-Champaign 201 North Goodwin Avenue Urbana, Illinois 61801-2302, USA

ABSTRACT

Algorithms, Design, Experimentation, Management, Performance, Security, Verification

1. INTRODUCTION

NSDI '13

A General Approach to Network Configuration Analysis

Ari Fogel Stanley Fung Luis Pedrosa Meg Walraed-Sullivan Ramesh Govindan Ratul Mahajan Todd Millstein

USENIX Association 12th USENIX Symposium on Networked Systems Design and Implementation (NSDI '15) 469

University of California, Los Angeles University of Southern California Microsoft Research

Abstract— We present an approach to detect network configuration errors, which combines the benefits of two prior approaches. Like prior techniques that analyze con-

Configuring networks is arduous because policy require can be complex and configuration languages are low-

Prior approaches Researchers have developed two

mon [7, 21, 36]. In a recent incident, for example, a mis-configuration led to a nation-wide outage that impacted all customers of Time Warner for over an hour [3].

The first approach directly analyzes network configuration files [2, 5, 7, 24, 25, 28, 34]. Such a static analysis occurs. Further, once a problem is flagged, the operator and ratios protectively, testore a new configuration is applied to the network, and it can naturally answer "what if" questions with respect to different environments (i.e., failures and route announcement from neighbors). A General Approach to Network Configuration Verification

into a logical formula that captures the stable states to which the network forwarding will converge as a result of interactions between routing protocols such as OSFF, BGP and static routes. It hen combines the formula with constraints that describe the intended property. If the combined formula is satisfiable, there exist a stable state of the network in which the property does not hold. Otherwise, no stable state (if any) violates the property. We used

SIGCOMM '11 NSDI '12 **NSDI** '15

and many, *many* more

SIGCOMM '17

CCS CONCEPTS

Network verification; Control plane analysis


classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or


KEYWORDS


Network verification has been wildly successful, academically *and* commercially











Forward Networks

Veriflow acquired by VMware

Intentionet acquired by Amazon

and, yet...

and, yet...

networks *still* go down due to misconfiguration

Either network operators...

Either network operators

use verification...

Either network operators

use verification

but it is not enough or not "in the right way"

Either network operators

use verification but it is not enough or not "in the right way"

do not use verification...

Either network operators

use verification but it is not enough or not "in the right way"

do not use verification...
voluntarily or not

Either network operators

use verification but it is not enough or not "in the right way"

do not use verification voluntarily or not

What's missing?

Network verification ain't a panacea

Network verification ain't a panacea

Network verification...

checks a restricted set of properties

and misses out on important ones

can be imprecise

over-/under-approximates behaviors


is not user-friendly

a perennial problem in formal methods

Verifying configurations was the easy part

My ongoing quest toward correct network operations

Formally Verified



More properties

beyond reachability

More coverage

beyond handcrafted models

Better usability

beyond human intervention

Verifying configurations was the easy part

My ongoing quest toward correct network operations

Formally Verified



More properties

beyond reachability

More coverage

beyond handcrafted models

Better usability

beyond human intervention

Existing verifiers typically only check forwarding-level properties, in the steady state

Existing verifiers typically only check forwarding-level properties, in the steady state

reachability, isolation, specific path(s) being followed...

Existing verifiers typically only check forwarding-level properties, in the steady state

once the network has converged, and assuming it converges

Operators also often care about other types of properties, as well as how long and how often these are violated

Verifying maximum link loads in a changing world

Tibor Schneider ETH Zürich Stefano Vissicchio
University College London

Laurent Vanbever *ETH Zürich*

Abstract

To meet ever more stringent requirements, network operators often need to reason about worst-case link loads. Doing so involves analyzing traffic forwarding after failures and BGP route changes. State-of-the-art systems identify failure scenarios causing congestion, but they ignore route changes.

We present Velo, the first verification system that efficiently finds maximum link loads under failures *and* route changes. The key building block of Velo is its ability to massively reduce the gigantic space of possible route changes thanks to (i) a router-based abstraction for route changes, (ii) a theoretical characterization of scenarios leading to worst-case link loads, and (iii) an approximation of input traffic matrices. We fully implement and extensively evaluate Velo. Velo takes only a few minutes to accurately compute all worst-case link loads in large ISP networks. It thus provides operators with critical support to robustify network configurations, improve network management and take business decisions.

1 Introduction

Link loads—how much traffic crosses each link—are a key indicator of network performance. High link loads, in partic-




Figure 1: Additional link loads can double due to route changes compared with link failures only. This plot shows the additional traffic on all the core links of an ISP network.


Reasoning about link loads is beyond the capabilities of existing network verifiers. Most of them [1, 4, 14, 39, 40, 42, 45, 50] do not support *performance* requirements such as maximum link loads, but restrict to *functional* requirements, such as the absence of blackholes and forwarding loops.

A couple of recent contributions [7, 27, 44] focus on assessing properties on link loads. Yet, they only consider network failures and assume fixed external routes, fitting controlled network environments such as data centers. For most Internet-connected networks, *both* failures and route changes

NSDI 2025

Recent systems find worst-case link loads under failures.

traffic matrices # failures



Find worst-case loads under arbitrary failures.


₹ Traffic also depends on *BGP* routing inputs.

QARC [1] or Yu [2]


^[1] Kausik Subramanian et al. "Detecting network load violations for distributed control planes". In: ACM SIGPLAN. 2020

^[2] Ruihan Li et al. "A General and Efficient Approach to Verifying Traffic Load Properties under Arbitrary k Failures". In: ACM SIGCOMM. 2024

Ignoring routing changes leads to underestimating worst-case loads.




Ignoring routing changes leads to underestimating worst-case loads.




Maximum additional link load, normalized by capacity

traffic matrices # failures # BGP changes




traffic matrices # failures # BGP changes




• A destination can be advertised by any subset of BGP neighbors.

traffic matrices # failures # BGP changes



- A destination can be advertised by any subset of BGP neighbors.
- Failures create dependencies between destinations.

traffic matrices # failures # BGP changes



- A destination can be advertised by any subset of BGP neighbors.
- Failures create dependencies between destinations.
- Over *one million* of destination prefixes.

Velo: Verify maximum link loads under failures and routing changes




Search space reduction:

A single egress router maximizes link loads.

Input size reduction:

Cluster destination with similar traffic patterns.

Velo finds the worst-case loads in 3 hours for all 1790 links in an ISP.





Probabilistic Verification of Network Configurations

Samuel Steffen ETH Zurich, Switzerland samuel.steffen@inf.ethz.ch

Timon Gehr ETH Zurich, Switzerland timon.gehr@inf.ethz.ch

Petar Tsankov ETH Zurich, Switzerland petar.tsankov@inf.ethz.ch

Laurent Vanbever ETH Zurich, Switzerland lvanbever@ethz.ch

ABSTRACT

Not all important network properties need to be enforced all the time. Often, what matters instead is the fraction of time / probability these properties hold. Computing the probability of a property in a network relying on complex inter-dependent routing protocols is challenging and requires determining all failure scenarios for which the property is violated. Doing so at scale and accurately goes beyond the capabilities of current network analyzers.

In this paper, we introduce NetDice, the first scalable and accurate probabilistic network configuration analyzer supporting BGP, OSPF, ECMP, and static routes. Our key contribution is an inference algorithm to efficiently explore the space of failure scenarios. More specifically, given a network configuration and a property ϕ , our algorithm automatically identifies a set of links whose failure is provably guaranteed not to change whether ϕ holds. By pruning these failure scenarios, NetDice manages to accurately approximate $P(\phi)$. NetDice supports practical properties and expressive failure models including correlated link failures.

We implement NetDice and evaluate it on realistic configurations. NetDice is practical: it can precisely verify probabilistic properties in few minutes, even in large networks.

CCS CONCEPTS

• Mathematics of computing → Probabilistic inference problems; • Networks \rightarrow Network properties.

KEYWORDS

Network analysis, Failures, Probabilistic inference, Cold edges

ACM Reference Format:

Martin Vechev ETH Zurich, Switzerland martin.vechev@inf.ethz.ch




Figure 1: Comparison of approaches for probabilistic network analysis in a network with 191 links and link failure probability 0.001. The confidence for sampling (Hoeffding's inequality) is $\alpha = 0.95$.


1 INTRODUCTION

Ensuring network correctness is an important problem that has received increased attention [1, 4, 12, 16, 19, 31, 40]. So far, existing approaches have focused on verifying "hard" properties, producing a binary answer of whether the property holds under all or a fixed set of failure scenarios.

Besides hard properties, network operators often need to reason about "soft" properties which can be violated for a small fraction of time (e.g. 0.01%). Among others, allowing properties to be violated allows for cheaper network designs, e.g. by reducing over-provisioning. Soft properties typically emerge when reasoning about compliance with Service Level Agreements (SLAs). SLAs can be defined with respect to any metric (e.g. path availability, average

SIGCOMM 2020

Probabilistic Verification



What is the *probability* of ?

high precision required

Service Level Agreements (SLA) "99.99% reachability"

Traffic Engineering "80% load-balanced"

"soft" properties

Attempts: Exploring Failures

Too expensive

Partial exploration

1 107 359

#scenarios for *four 9s*, 191 links, $p_{link failure} = 0.001$ Estimation via sampling


738 M


Hoeffding, $\alpha = 0.95$





1854


≈600x reduction






































Runtime

Single-flow (e.g. Reachability)

Few minutes for 100s of links for four 9s

For 80% of scenarios, > 50% of links are



Transient Forwarding Anomalies and How to Find Them

ROLAND SCHMID, ETH Zürich, Switzerland TIBOR SCHNEIDER, ETH Zürich, Switzerland GEORGIA FRAGKOULI, ETH Zürich, Switzerland LAURENT VANBEVER, ETH Zürich, Switzerland

Analyzing transient violations of reachability—that happen while routing protocols are re-converging—helps in improving network availability and offering more precise SLAs. The key challenge is analyzing transient violations *accurately*, as they can be short-lived, for *all* affected prefix destinations, and *practically*, without worsening the network's performance. Existing approaches fail to address at least one of these goals: measurement approaches are accurate but only for the prefixes they can probe or observe traffic for, while techniques that estimate the convergence time use the same crude proxy for all prefixes.

To achieve all three goals, we present TRIX, a system that infers transient violation times for BGP events from logged routing events or collected BGP messages. TRIX' key insight is that we do not need to probe all destinations if we use available information to infer the router-local forwarding state, for all destinations, and reconstruct the network-wide violations from router-level state. However, the logged events contain control-plane information that is inaccurate in terms of the content and the times of the forwarding updates, while reconstructing network-wide violations requires reasoning about the flow of traffic through the network. TRIX solves these challenges by simulating the BGP control-plane, modeling the FIB-update rate, and combining the state across routers with propagation delays. To evaluate TRIX, we implement a testbed that relies on a programmable switch and uses 12 real routers. Our evaluation shows that TRIX' inferred reachability violation times are on average within 13–25 ms from the ground truth, and inference scales to large networks.

CCS Concepts: • Networks \rightarrow Protocol testing and verification; Routing protocols; Network reliability; Formal specifications.

Additional Key Words and Phrases: Forwarding Anomalies, Routing Convergence, Transient Violations

ACM Reference Format:

Roland Schmid, Tibor Schneider, Georgia Fragkouli, and Laurent Vanbever. 2025. Transient Forwarding Anomalies and How to Find Them. *Proc. ACM Netw.* 3, CoNEXT2, Article 10 (June 2025), 23 pages. https://doi.org/10.1145/3730973

CONEXT 2025

Most network verifiers can only assess correctness properties when the network has converged

Most network verifiers can only assess correctness properties when the network has converged

Corollary

As the network converges, e.g. after a link failure or a route update, important correctness properties might be violated

Most network verifiers can only assess correctness properties when the network has converged

Corollary

As the network converges, e.g. after a link failure or a route update, important correctness properties might be violated

Research question

How long are these transient violations? How often do they appear?

Accurately estimating these violation times is hard

Routing events can affect any prefix(es) many

Violations can be short-lived, or not

from milliseconds to many seconds

Accurately estimating these violation times is hard

Routing events can affect any prefix(es) many

Violations can be short-lived, or not

from milliseconds to many seconds

→ Active probing is not realistic


Our system infers violation times accurately and for all prefixes, from widely available control-plane logs

Our system infers violation times accurately and for all prefixes, from widely available control-plane logs


BGP events, RIB events, FIB writes, ...

The key challenge is to bridge the gap between control plane events and their effects in the data plane (if any)

Our system bridges this gap by modeling the RIB-to-FIB bottleneck




Our system achieves an average accuracy of 13-25ms



Verifying configurations was the easy part

My ongoing quest toward correct network operations

Formally Verified



More properties

beyond reachability

More coverage

beyond handcrafted models

Better usability

beyond human intervention

A network verifier can only be blindly trusted if its analysis is **sound** and **complete**

A network verifier can only be blindly trusted if its analysis is **sound** and **complete**

sound

Reports all bugs

complete

Reports only bugs

Ensuring both is often impossible (Rice's theorem)

verifiers need to accurately model...

all protocols and all their behaviors BGP, OSPF, IS-IS, EIGRP, ...

for all vendors, devices and OSes Cisco, Juniper, Brocade, Arista, ...

Ensuring both is often impossible (Rice's theorem)

verifiers need to accurately model...

all protocols and *all* their behaviors BGP, OSPF, IS-IS, EIGRP, ...

for all vendors, devices and OSes Cisco, Juniper, Brocade, Arista, ...

... including any bugs




Photo: IEEE Computer Society

"Beware of bugs in the above code;
I have only proved it correct,
not tried it."

—Donald Knuth

detect model inaccuracies

build accurate models

automatically

detect model inaccuracies

build accurate models

automatically

Metha: Network Verifiers Need To Be Correct Too!

Rüdiger Birkner* Tobias Brodmann* Petar Tsankov Laurent Vanbever Martin Vechev

*These authors contributed equally to this work.

ETH Zürich

Abstract

Network analysis and verification tools are often a godsend for network operators as they free them from the fear of introducing outages or security breaches. As with any complex software though, these tools can (and often do) have bugs. For the operators, these bugs are not necessarily problematic except if they affect the precision of the model as it applies to their specific network. In that case, the tool output might be wrong: it might fail to detect actual configuration errors and/or report non-existing ones.

In this paper, we present Metha, a framework that systematically tests network analysis and verification tools for bugs in their network models. Metha automatically generates syntactically- and semantically-valid configurations; compares the tool's output to that of the actual router software; and detects any discrepancy as a bug in the tool's model. The challenge in testing network analyzers this way is that a bug may occur very rarely and only when a specific set of configuration statements is present. We address this challenge by leveraging grammar-based fuzzing together with combinatorial testing to ensure thorough coverage of the search space and by identifying the minimal set of statements triggering the bug through delta debugging.

We implemented Metha and used it to test three well-known

This fictitious situation illustrates an intrinsic problem with validation technologies: their results can only be completely trusted if their analysis is sound and complete. As with any complex software though, these tools can (and often do) have bugs. To be fair, this is not surprising: building an accurate and faithful network analysis tool is extremely difficult. Among others, one not only has to precisely capture all the different protocols' behaviors, but also all of the quirks of their specific implementations. Unfortunately, every vendor, every OS, every device can exhibit slightly different behaviors under certain conditions. For all it takes, these behaviors might be the results of bugs themselves. And yet, failing to accurately capture these behaviors—as we show—can lead to incorrect and possibly misleading analysis results.

A fundamental and practical research question is therefore: How can developers make sure that their network analysis and verification tools are correct?

Metha We introduce Metha, a system that thoroughly tests network analysis and verification tools to find subtle bugs in their network models using black-box differential testing. Metha automatically finds model discrepancies by generating input configurations and comparing the output of the tool under test with the output produced by the actual router software. For every discovered discrepancy, Metha provides a minimal


NSDI 2021

Metha systematically tests network verifiers through automated configuration generation

Metha



Supply configurations and compare results







Metha: Automated Testing of Network Analyzers

- Sensible configurations
 satisfying configuration dependencies
- 2 Systematic exploration covering the search space thoroughly
- Actionable feedback isolating the problematic statements

Metha found bugs in all three tested tools

	# bugs	crash	silent
Batfish	30	5	25
NV	30	5	25
C-BGP	3	0	3

detect model inaccuracies

build accurate models

automatically

Learning to Configure Computer Networks with Neural Algorithmic Reasoning

Luca Beurer-Kellner^{1,*} M

Martin Vechev¹

Laurent Vanbever¹

Petar Veličković²

¹ETH Zurich, Switzerland

²DeepMind

https://github.com/eth-sri/learning-to-configure-networks

Abstract

We present a new method for scaling automatic configuration of computer networks. The key idea is to relax the computationally hard search problem of finding a configuration that satisfies a given specification into an approximate objective amenable to learning-based techniques. Based on this idea, we train a neural algorithmic model which learns to generate configurations likely to (fully or partially) satisfy a given specification under existing routing protocols. By relaxing the rigid satisfaction guarantees, our approach (i) enables greater flexibility: it is protocol-agnostic, enables cross-protocol reasoning, and does not depend on hardcoded rules; and (ii) finds configurations for much larger computer networks than previously possible. Our learned synthesizer is up to $490\times$ faster than state-of-the-art SMT-based methods, while producing configurations which on average satisfy more than 92% of the provided requirements.

1 Introduction

Configuring large-scale networks is a challenging and important task as network configuration mistakes regularly lead to massive internet-wide outages affecting millions (resp. billions²) of Internet users [35, 25]. Typically, network operators provide a router-level configuration W which, after applying protocols such as shortest-path routing, induces a certain forwarding behaviour FWD as illustrated in Figure 1. As this remains a challenging task, much recent research has focused on automating configuration by leveraging synthesis techniques [15, 5, 31]: A synthesizer is used to

NeurIPS 2022

Can we learn how to configure a network?

Can we learn how to configure a network? Yes, to an extent

Train a graph-based neural model to invert network computations

Using generated pairs of (cfgs, specs) simulate the cfg, extract the forwarding state

Fully automatic!

Neural-based configuration synthesis is much faster but does not yet achieve 100% accuracy

Result BGP/OSPF configuration synthesis

- Learning-based synthesis is much faster than SOTA SMT tools (490x) while still maintaining good consistency (92% of req.)
- Other benefits: UNSAT specification, sample variations

Table 3: Comparing consistency and synthesis time of our method (Neural) with the SMT-based NetComplete. The notation n/8 TO indicates the number of timed out runs out of 8 (25+ minutes).

# Requirements		NetComplete (s)	Neural CPU (s)	Speedup	Ø Consistency	Full Matches
2 reqs.	S	18.07s±14.55	0.72s±0.54	25.2x	0.97±0.09	7/8
-	M	60.86s±33.39	$3.18s \pm 4.32$	19.1x	0.94 ± 0.13	6/8
	L	$1389.48s \pm 312.58$ 7/8 TO	$24.25s \pm 28.35$	57.3x	0.99 ± 0.03	7/8
8 reqs. S M L	S	247.69s±436.90	1.25s±1.02	198.7x	0.96±0.08	6/8
	M	>25m 8/8 TO	$4.55s \pm 4.30$	329.8x	0.97 ± 0.04	4/8
	L	>25m 8/8 to	$31.28s \pm 28.53$	48.0x	0.97 ± 0.05	5/8
16 reqs. S M L	S	1416.83s±235.25 7/8 TO	2.88s±1.66	492.0x	0.92±0.06	1/8
	M	>25m 8/8 TO	$6.53s\pm5.10$	229.8x	0.95 ± 0.05	2/8
	L	>25m 8/8 TO	87.99s±141.97	17.0x	0.95 ± 0.03	2/8



Verifying configurations was the easy part My ongoing quest toward correct network operations

Formally Verified



More properties

beyond reachability

More coverage

beyond handcrafted models

Better usability

beyond human intervention

To go mainstream, network verification needs to be more usable even assuming more properties and coverage

Clarify what to verify

Deploy verified configurations

Simplify the "before"

Simplify the "after"

Clarify what to verify

Simplify the "before"

Deploy verified configurations

Config2Spec: Mining Network Specifications from Network Configurations

Rüdiger Birkner¹ Dana Drachsler-Cohen^{2*} Laurent Vanbever¹ Martin Vechev¹

¹ETH Zürich ²Technion

Abstract

Network verification and configuration synthesis are promising approaches to make networks more reliable and secure by enforcing a set of policies. However, these approaches require a formal and precise description of the intended network behavior, imposing a major barrier to their adoption: network operators are not only reluctant to write formal specifications, but often do not even know what these specifications are.

We present *Config2Spec*, a system that automatically synthesizes a formal specification (a set of policies) of a network given its configuration and a failure model (e.g., up to two link failures). A key technical challenge is to design a synthesis algorithm which can efficiently explore the large space of possible policies. To address this challenge, *Config2Spec* relies on a careful combination of two well-known methods: data plane analysis and control plane verification.

Experimental results show that *Config2Spec* scales to mining specifications of large networks (>150 routers).

1 Introduction

Consider the task of a network operator who—tired of human-induced network downtimes—decides to rely on formal meth-

homegrown over years, by a team of network engineers (some of which do not even work there anymore).

This situation illustrates the difficulty of writing network specifications. Akin to software specifications, formal specifications are hard to write (as hard as writing the program in the first place [20]), debug, and modify [2,21]. Yet, without easier ways to provide network specifications, network verification and synthesis are unlikely to get widely deployed.

Config2Spec We introduce Config2Spec, a system that automatically mines a network's specification from its configurations and a failure model (e.g., up to k failures). Config2Spec is precise: it returns all policies that hold under the failure model (no false negatives) and only those (no false positives).


Challenges Mining precise network specifications is challenging as it involves exploring two exponential search spaces: (i) the space of all possible policies, and (ii) the space of all possible network-wide forwarding states. The challenge stems from the fact that individually exploring each of the search spaces can be prohibitive: a search for the true policies is hard since they are a small fraction of the policy space, while a search for the violated policies is hard since these require witnesses (data planes), which are often sparse.

Insights *Config2Spec* addresses the above challenges by com-

NSDI 2020

Internet2's specification with its 10 routers consists of ~4000 policy predicates.

Config2Spec mines the network's full specification from its configuration and the required failure tolerance



Clarify what to verify

Deploy verified configurations

Simplify the "after"

Taming the transient while reconfiguring BGP

Tibor Schneider ETH Zurich sctibor@ethz.ch Roland Schmid ETH Zurich roschmi@ethz.ch Stefano Vissicchio University College London s.vissicchio@ucl.ac.uk Laurent Vanbever ETH Zurich lvanbever@ethz.ch

ABSTRACT

BGP reconfigurations are a daily occurrence for most network operators, especially in large networks. Yet, performing safe and robust BGP reconfiguration changes is still an open problem. Few BGP reconfiguration techniques exist, and they are either (i) unsafe, because they ignore transient states, which can easily lead to invariant violations; or (ii) impractical, as they duplicate the entire routing and forwarding states, and require special hardware.

In this paper, we introduce Chameleon, the first BGP reconfiguration framework capable of maintaining correctness throughout a reconfiguration campaign while relying on standard BGP functionalities and minimizing state duplication. Akin to concurrency coordination in distributed systems, Chameleon models the reconfiguration process with happens-before relations. This modeling allows us to capture the safety properties of transient BGP states. We then use this knowledge to precisely control the BGP route propagation and convergence, so that input invariants are provably preserved at any time during the reconfiguration.

We fully implement Chameleon and evaluate it in both testbeds and simulations, on real-world topologies and large-scale reconfiguration scenarios. In most experiments, our system computes reconfiguration plans within a minute, and performs them from start to finish in a few minutes, with minimal overhead.

CCS CONCEPTS

• Networks → Network management; Routing protocols; Network control algorithms; Network reliability.

KEYWORDS

SIGCOMM 2023

Border Gateway Protocol (BGP), reconfiguration, network update, convergence, scheduling

ACM Reference Format:

Tiber Schneider Poland Schmid Stefano Vissischia and Laurent Vanhave




Figure 1: BGP reconfigurations often lead to disruptions, even when using recent reconfiguration frameworks such as Snowcap [28]. Here, Snowcap transiently violates two invariants (reachability and waypointing). In contrast, Chameleon reconfigures the network without violating any.

1 INTRODUCTION

Much has been written about network reconfigurations, their frequency [12, 20, 28, 32, 36] and their disruptiveness [18, 22, 28]. Yet, reconfiguration-induced downtimes *still* happen. In fact, Alibaba recently stated that the *majority* of their network outages resulted from configuration updates [22].

Among all reconfiguration scenarios, BGP ones are special be-

Network reconfiguration

Network reconfiguration

Given specification φ



Network reconfiguration

Given specification arphi and an initial configuration \mathcal{C}_i final


Network reconfiguration

Given specification $\,arphi\,$ and $\,$ an initial configuration $\,{\cal C}_i\,$ final

Return $\mathcal{C}_i, \mathcal{C}_a, \mathcal{C}_b, \ldots \mathcal{C}_f \models arphi$


Not exactly a new problem...

Not exactly a new problem...




Existing techniques...

- duplicate the entire control plane;
- temporarily "freeze" it"(cannot react to failures)



Chameleon reconfigures networks in-place, one router at a time, correctly, and within 5 minutes even for large networks



Verifying configurations was the easy part My ongoing quest toward correct network operations

Formally Verified



More properties

beyond reachability

More coverage

beyond handcrafted models

Better usability

beyond human intervention

Configuring a network is only a small part of network operations as a whole

Configuring a network is only a small part of network operations as a whole

Network operations

Configure

Design

Monitor

Optimize

Secure

Troubleshoot

and *many* others...

Similarly to configuring,

many of these tasks are bottlenecked by human reasoning

Configure

Design

Monitor

Optimize

Secure

Troubleshoot

model-based

model-less

"AI"

model-based

model-less

"AI"

Guarantees

Coverage

Explainability

Overhead

model-based

model-less

"Al"

Guarantees

strong

Coverage

reduced

Explainability

high

Overhead

high

upstream

	model-based	model-less "AI"
Guarantees	strong	few
Coverage	reduced	high
Explainability	high	poor
Overhead	high upstream	high downstream

	model-based	model-less "Al"
Guarantees	strong	few
Coverage	reduced	high
Explainability	high	poor
Overhead	high upstream	high downstream

Can we get the best of both worlds?

model-based X model-less

POSTER: Continual Benchmarking of LLM-Based Systems on Networking Operations

Ioannis Protogeros ETH Zürich iprotogeros@ethz.ch Laurent Vanbever ETH Zürich lvanbever@ethz.ch

Abstract

The inherent complexity of operating modern network infrastructures has led to growing interest in using Large Language Models (LLMs) to support network operators, particularly in the area of Incident Management (IM). Yet, the absence of standardized benchmarks for evaluating such systems poses challenges in tracking progress, comparing approaches, and uncovering their limitations. As LLM-based tools become widespread, there is a clear need for a comprehensive benchmarking suite that reflects the diversity and complexity of operational tasks encountered in real-world networks.

This poster outlines our vision for designing such a modular benchmarking suite. We describe an approach for generating operational tasks of varying complexity and discuss how to evaluate LLMs on these tasks and assess system-level performance. As a preliminary evaluation, we benchmark three LLMs — GPT-4.1, Gemini 2.5-Pro, and Claude 3.7 Sonnet — across over 100 test cases and two pipeline variants.

CCS Concepts

• Networks \rightarrow Network management; • Computing methodologies \rightarrow Knowledge representation and reasoning; Artificial intelligence.

Keywords

Large Language Models, Network Management, Benchmarking, Incident Management

ACM Reference Format:

Ioannis Protogeros and Laurent Vanbever. 2025. POSTER: Continual Benchmarking of LLM-Based Systems on Networking Operations. In *ACM SIG-COMM 2025 Conference (SIGCOMM Posters and Demos '25), September 8–11, 2025, Coimbra, Portugal.* ACM, New York, NY, USA, 3 pages. https://doi.org/10.1145/3744969.3748425

well-defined tasks of **varying complexity** remains a challenging task in the inherently complex setting of Network IM.

Focusing on the case of misconfigured networks disrupting their intended behaviour, we pose the following Research Questions (RQs) that capture the requirements of a benchmark in our task context:

RQ1: How can we automatically generate realistic and complex fault scenarios and quantify their impact on network behaviour? Modeling disruption severity and resolution difficulty from misconfigurations requires establishing nonlinear causal relationships. Capturing this complexity is paramount for generating challenging and meaningful test cases.


RQ2: (i) How should network state be encoded for LLM-based systems, and (ii) which solution pipelines are most effective? Various approaches are being proposed, from the handling of raw network data [4, 6] to the definition of structured workflows integrating specialized tools [3]. These strategies require evaluation under a unified and extensible testbed to ensure comparability and relevance.

RQ3: How do we meaningfully assess an LLM's proposed fix against a "ground-truth", intended network behavior? Using data to represent the network states, we need to distill metrics that succinctly describe a remedy's efficacy.

This work identifies key design considerations for automated LLM-centered system evaluation in Network Incident Management. We present a system that allows the *continual* incorporation of the advancements related to these open research questions. We also highlight the importance of extensibility when evaluating complex workflows that cannot be effectively addressed with a monolithic $Input \rightarrow LLM \rightarrow Output$ design.


2 Proposed Framework and Design Considerations

SIGCOMM 2025



Verifying configurations was the easy part

My ongoing quest toward correct network operations





focus on this next-

Laurent Vanbever

nsg.ethz.ch | netfabric.ai

FMANO

Mon Sept 8 2025