### Self-driving/monitoring networks

in the age of deep network programmability





Laurent Vanbever

nsg.ee.ethz.ch

TMA

June 19 2019

## 



Paul Baran (1926–2011)

American electrical engineer

created the notion of a distributed network which could maintain communications in the face of a thermonuclear attack

inventor of packet switching(with Donald Davies)

#### On distributed communication networks

Paul Baran—Sept. 1962

#### Introduces the concept of

- packet switching
- distributed routing
- reliable transport

among many others...

#### ON DISTRIBUTED COMMUNICATIONS NETWORKS

#### Paul Baran\*

The RAND Corporation, Santa Monica, California

The previous paper\*\* described how redundancy of coding can be used to build efficient digital data links out of transmission links of variable and often less than presently useful quality. An arbitrarily low over-all error rate can be purchased with a modest redundancy of coding and clever terminal equipment. But even links with low error rates can have less than perfect reliability.

We should like to extend the remarks of the previous paper and address ourselves to the problem of building

\*Any views expressed in this paper are those of the author. They should not be interpreted as reflecting the views of The RAND Corporation or the official opinion or policy of any of its governmental or private research sponsors. Papers are reproduced by The RAND Corporation as a courtesy to members of its staff.

This paper was prepared for presentation at the First Congress of the Information Systems Sciences, sponsored by The MITRE Corporation and the USAF Electronic Systems Division, November, 1962.

The writer is indebted to John Bower for his suggestions that switching in any store-and-forward system can be described by a model of a postmaster at a blackboard. Programming assistance provided by Sharla Boehm, John Derr, and Joseph Smith is gratefully acknowledged.

\*\*A prior paper was presented by Paul Rosen and Irwin Lebow of MIT Lincoln Laboratories, discussing redundancy of coding on a single link, "Low Error Efficient Digitial Communications Links," First Congress on the Information Systems Sciences, McGraw-Hill, New York, 1962.

#### HOT-POTATO HEURISTIC ROUTING DOCTRINE


To achieve real-time operation it is desirable to respond to change in network status as quickly as possible so we shall seek to derive the network status information directly into each message block.

Each standardized message block contains a "to" address, a "from" address, a handover number tag, and error detecting bits together with other housekeeping data. The message block is analogous to a letter. The "from" address is equivalent to the return address of the letter.

The handover number is a tag in each message block set to zero upon initial transmission of the message block into the network. Every time the message block is passed on, the handover number is incremented. The handover number tag on each message block indicates the length of time in the network or path length. This tag is somewhat analogous to the cancellation date of a conventional letter.

#### INDUCTIVE DETERMINATION OF BEST PATH

Assuming symmetrical bi-directional links, the postman can infer the "best" paths to transmit mail to any station merely by looking at the cancellation time or the equivalent handover number tag. If the postman sitting San Francisco, he would find that letters from San Francisco arriving from channels to the west would come in with later cancellation dates than if such letters had



Thanks to Paul Barlan et al.

the Internet infrastructure is extremely resilient

ability to route packets around failures

(not necessarily fast though)

Thanks to Paul Barlan et al.
the Internet infrastructure is extremely resilient

... at least when it comes to thermonuclear wars...

Thanks to Paul Barlan et al.
the Internet infrastructure is extremely resilient


... at least when it comes to thermonuclear wars...

but how does it fare against, say...

Thanks to Paul Barlan et al.
the Internet infrastructure is extremely resilient

... at least when it comes to thermonuclear wars...

but how does it fare against, say... us humans?



# Google accidentally broke the internet throughout Japan

A mistake led to internet outages for about half of the country.





#### 27 August 2017

Google made a configuration mistake which caused their Chicago point-of-presence to wrongly advertise 160k IP prefixes to its neighbors.

Google made a configuration mistake which caused their Chicago point-of-presence to wrongly advertise 160k IP prefixes to its neighbors.


These advertisements propagated in the Internet and got picked up by Japanese giants (IIJ and KDDI) which started to direct local Japanese traffic to Google.

## Tokyo to Nagoya (normally)



#### Tokyo to Nagoya via... Chicago?!

#### A 17x increased latency!



Google made a configuration mistake which caused their Chicago point-of-presence to wrongly advertise 160k IP prefixes to its neighbors.

These advertisements propagated in the Internet and got picked up by Japanese giants (NTT and KDDI) which started to direct local, Japanese traffic to Google.

The outage in Japan *only* lasted a couple of hours but was so severe that the country's ministries wanted carriers to report on what went wrong.

This is far from being an isolated event...


Forbes / Personal Finance

The Little Black Book of Billionaire Secrets

United Airlines Blames Router for Grounded Flights

#### 'Configuration Error' Blamed for AWS Outage

**By David Ramel 08/12/2015** 



News. Today -

**Amazon's massive AWS outage was** caused by human error

One incorrect command and the whole internet suffers. By Jason Del Rey | @DelRey | Mar 2, 2017, 2:20pm EST

**Data Centre** Networks

Level3 switch config

By Barry Amundson on Aug 15, 2018 at 4:43 p.m.

Diuliue affected for US-wide VoIP blackout

CenturyLink: 750 calls to 911 missed during Aug. 1 outage caused by human error in Minnesota, North **Dakota** 

affected Comcast, Spectrum, Verizon and AT&T customers

**Data Centre** Networks

CloudFlare apologizes for Telia screwing you over

### Unhappy abou Facebook struggles to deal with epic outage

By Kieren McCarthy in






By Donie O'Sullivan and Heather Kelly, CNN Business Updated 0654 GMT (1454 HKT) March 14, 2019

"Human factors are responsible for 50% to 80% of network outages"

## A perhaps ironic consequence is that the Internet works better during the week-ends



% of route leaks

source: Job Snijders, 2008–2016

"Human factors are responsible for 50% to 80% of network outages"

"Human factors are responsible

for

"Human factors are responsible

for >90% of car accidents

Self-Driving Car

### Self-Driving Car

Wikipedia A

A vehicle that is capable of monitoring its environment and moving with little or no human input

### Self-Driving Car

Wikipedia A vehicle that is capable of

monitoring its environment and

moving with little or no human input

Promise A drastic reduction in the number of (fatal) accidents

Self-Driving Car

Self-Driving

Self-Driving Network

# Enters... Self-Driving Network

Definition

A network that is capable of monitoring its environment and adapting its behavior accordingly with little or no human input

# Enters... Self-Driving Network

Definition

A network that is capable of monitoring its environment and adapting its behavior accordingly with little or no human input

Questions How do we build and deploy such networks?


# Enters... Self-Driving Network

Definition A network that is capable of monitoring its environment and adapting its behavior accordingly

Questions How do we build and deploy such networks?

with little or no human input


## Until recently, innovating in networks was hard because devices were completely locked down





Cisco™ device

Things are changing though!


## Networks are on the verge of a paradigm shift towards deep programmability












Barefoot Tofino 12.8 Tbps

programmable network switch


NetFPGA SUME

Netronome Agilio CX

100 Gbps programmable network card



## Reprogrammable network hardware allows to completely redefine the forwarding logic



## Programmable networks can be made "self-driving"

#### Programmable devices can

- measure
- perform statistical inference
- adapt their forwarding decisions

at line rate, on a per-packet basis

## Enters... Self-Driving Network

A network that is capable of Definition

monitoring its environment and

adapting its behavior accordingly

with little or no human input

How do we build and deploy such networks? Questions

#### Levels of autonomy in self-driving cars

level 0 no automation driver assistance human monitors the environment partial automation conditional automation 3 system monitors human as fallback high automation full automation no more human

### Self-driving/monitoring networks

in the age of deep network programmability

operator assistance

2 partial automation

Part I assisting operators

3 conditional automation

4 high automation

Part II taking control

full automation

too futuristic? 🙂

Human Operator

Insights Specifications

Self-Driving Logic

Sensors Actuators

Live Network

Net2Text NSDI'18

Bayonet PLDI'18

SDNRacer SWIFT PLDI'16 SIGCOMM'17

Blink NSDI'19

Stroboscope NSDI'18

SP-PIFO NSDI'20 Human Operator

Insights | Specifications

Self-Driving Logic

Sensors Actuators

Live Network

Config2Spec NSDI'20

SyNET CAV'17

NetComplete NSDI'18

Fibbing SIGCOMM'15

SDX NSDI'16 SIGCOMM'14 Net2Text NSDI'18

Bayonet PLDI'18

SDNRacer PLDI'16 SWIFT SIGCOMM'17

Blink NSDI'19

Stroboscope NSDI'18

SP-PIFO NSDI'20 Human Operator

Insights | Specifications

Self-Driving Logic

Sensors Actuators

Live Network

Config2Spec NSDI'20

SyNET CAV'17

NetComplete NSDI'18

Fibbing SIGCOMM'15

SDX NSDI'16 SIGCOMM'14

### Self-driving/monitoring networks

in the age of deep network programmability

operator assistance

2 partial automation

Part I assisting operators

3 conditional automation

4 high automation

Part II taking control

full automation

too futuristic? 🙂

### Self-driving/monitoring networks

in the age of deep network programmability

operator assistance

2 partial automation

3 conditional automation

4 high automation

full automation

Part I assisting operators

Part II taking control

too futuristic? 🙂

### Stroboscope: Declarative Network Monitoring on a Budget







**Tobias Bühler** 



Ingmar Poese




Stefano Vissicchio




Laurent Vanbever

USENIX Symposium on Networked Systems Design and Implementation. April 2018.


### Consider this example ISP network topology



### What is the ingress router for this packet arriving at router D?




### Which paths does the traffic follow?




### Which paths does the traffic follow?


Tracking flows network-wide requires to match measurements across multiple vantage points




## Is traffic load-balanced as expected?



### Is the latency acceptable?




#### Are there losses?



#### Are there losses?



Fine-grained data-plane performance metrics require packet-level visibility over individual flows



### Fined-grained network monitoring is widely researched

Gigascope [SIGMOD'03]

Planck [SIGCOMM'14]

Everflow [SIGCOMM'15]

Compiling Path Queries [NSDI'16]

Trumpet [SIGCOMM'16]

## Fined-grained ISP network monitoring poses unique and unmet challenges

No control over end hosts

Gigascope [SIGMOD'03]

Planck [SIGCOMM'14]

Everflow [SIGCOMM'15]

Compiling Path Queries [NSDI'16]

Trumpet [SIGCOMM'16]

## Fined-grained ISP network monitoring poses unique and unmet challenges

No control over end hosts

Limited data-plane flexibility

Gigascope [SIGMOD'03]

Planck [SIGCOMM'14]

Everflow [SIGCOMM'15]

Compiling Path Queries [NSDI'16]

**Trumpet [SIGCOMM'16]** 

## Fined-grained ISP network monitoring poses unique and unmet challenges

No control over end hosts

Limited data-plane flexibility

Limited monitoring bandwidth

Gigascope [SIGMOD'03]

Planck [SIGCOMM'14]

Everflow [SIGCOMM'15]

Compiling Path Queries [NSDI'16]


Trumpet [SIGCOMM'16]

### Stroboscope: Declarative Network Monitoring on a Budget




- Collecting traffic slices to monitor networks
- Adhering to a monitoring budget
- Using Stroboscope today


### Consider the following flow of packets




### Consider the following flow of packets




### Stroboscope activates mirroring for the flow




### Packets are copied and encapsulated towards the collector




### The mirroring rule is deactivated after a preset delay




### Stroboscope stores the traffic slice for analysis




### Stroboscope periodically toggles the mirroring rule




### Stroboscope periodically toggles the mirroring rule



### Stroboscope periodically toggles the mirroring rule



### Stroboscope collects multiples traffic slices over time



Collector34910

# Analyzing matching packets across traffic slices enables fine-grained measurements at scale

# Analyzing matching packets across traffic slices enables fine-grained measurements at scale

Forwarding paths discovery, timestamp reconstruction, payload inspection, ...

## Stroboscope defines a declarative requirement language

MIRROR 1.2.3.0/24 ON [A B C D], [A E C D]

MIRROR 1.2.3.0/24 ON [A -> D]


CONFINE 1.2.3.0/24 ON [A B E C D]

CONFINE 1.2.3.0/24 [A -> D]

MIRROR 1.2.3.0/24 on [-> D]

CONFINE 1.2.3.0/24 ON [-> D]

USING 15 Mbps DURING 500 ms EVERY 5 s



## Stroboscope defines two types of queries

**MIRROR** 

CONFINE


## Stroboscope defines two types of queries

MIRROR

CONFINE


## MIRROR queries reconstruct the path taken by packets

MIRROR 1.2.3.0/24 ON [A B C D]




## Fewer mirroring rules reduces bandwidth usage

MIRROR 1.2.3.0/24 ON [A B C D]



## Too few mirroring rules creates ambiguity


MIRROR 1.2.3.0/24 ON [A B C D]



## Too few mirroring rules creates ambiguity

MIRROR 1.2.3.0/24 ON [A B C D]

The **Key-Points Sampling** algorithm minimizes mirroring rules and guarantees non-ambiguous reconstructed paths




## Stroboscope defines two types of queries

**MIRROR** 

CONFINE


## CONFINE queries mirror packets leaving a confinement region

CONFINE 1.2.3.0/24 ON [A B E C D]




## Fewer mirroring rules minimizes control-plane overhead

CONFINE 1.2.3.0/24 ON [A B E C D]



### The lower bound is a multi-terminal node cut


CONFINE 1.2.3.0/24 ON [A B E C D]



#### The lower bound is a multi-terminal node cut

CONFINE 1.2.3.0/24 ON [A B E C D]

The **Surrounding** algorithm minimizes mirroring rules and guarantees to mirror any packet leaving the confinement region



## Stroboscope: Declarative Network Monitoring on a Budget



- Collecting traffic slices to monitor networks
- Adhering to a monitoring budget
- Using Stroboscope today


## Stroboscope works with currently deployed routers

- Most vendors provide traffic mirroring and encapsulation primitives
- The collector activates mirroring for a flow by updating one ACL


Routers autonomously deactivate mirroring rules using timers

Traffic slices can be as small as **23 ms** on our routers (Cisco C7018)


## Stroboscope tracks the rate of mirrored traffic in real time




## Measurement campaigns are stopped early if the estimated demand are exceeded




## Exceeding the total budget schedules the query once per measurement campaign



## Stable recorded traffic rates are used for future estimations



## Stroboscope exceeds the monitoring budget for at most one timeslot




## Stroboscope: Declarative Network Monitoring on a Budget



- Traffic slicing as a first-class data-plane primitive
- Strong guarantees on budget compliance and measurement accuracy
- Measurement analysis decoupled from measurement collection

## Net2Text: Query-guided Network Captioning







Dana Drachsler-Cohen



Martin Vechev



Laurent Vanbever

USENIX Symposium on Networked Systems Design and Implementation. April 2018.





Type a message...



Where is the traffic...



question in natural language

Where is the traffic leaving in NEWY coming from?



Type a message...



Where is the traffic leaving in NEWY coming from?







Type a message...



Where is the traffic leaving in NEWY coming from?





The traffic enters mostly in PHIL and goes to Youtube and Netflix.

Type a message...

summary in natural language



question in natural language

Where is the traffic leaving in NEWY coming from?





The traffic enters mostly in PHIL and goes to Youtube and Netflix.

Type a message...

summary in natural language

# Finding *a* summary of the network-wide forwarding state is simple

# Finding *a* summary of the network-wide forwarding state is simple

Traffic is forwarded.

# Finding *a* summary of the network-wide forwarding state is simple

Traffic from LOSA to 35.184.0.0/19, which is owned by Google, is leaving the network in CHIC and takes the path SUNV, DENV, KSCY, INDI to CHIC.

# Finding a good summary of the network-wide forwarding state is hard

Summarization is a multi-objective optimization problem


#### Coverage

amount of data described by the summary


# Coverage amount of data described by the summary

Explainability
amount of detail
provided by the summary


#### Coverage



Explainability




### Coverage



Explainability

Score

Weighted sum of the amount of traffic covered by each path specification in the summary.



#### Explainability

weights based on level of detail of the path specification

Score

Weighted sum of the amount of traffic covered by each path specification in the summary.

Score Weighted sum of the amount of traffic covered by

each path specification in the summary.

Goal Find path specifications that maximize the score.


Score Weighted sum of the amount of traffic covered by

each path specification in the summary.


Goal Find *k* path specifications each of size at most *t* 

that maximize the score.

# The search space is exponential in the number of path specifications and feature values



# Net2Text reduces the search space to solutions that balance coverage and explainability



### Self-driving/monitoring networks

in the age of deep network programmability

operator assistance

2 partial automation

Part I assisting operators

3 conditional automation

4 high automation

Part II taking control

full automation

too futuristic? 🙂

#### Part II: Taking control

data-driven

convergence

applications frameworks methods

monitoring/inference

some of our challenges

lying ahead

### Part II: Taking control

applications

frameworks

methods

data-driven convergence

#### Blink

### Fast Connectivity Recovery Entirely in the Data Plane



Thomas Holterbach



Edgar Costa Molero



Maria Apostolaki



Alberto Dainotti




Stefano Vissicchio



Laurent Vanbever

USENIX Symposium on Networked Systems Design and Implementation. February 2019.

# Internet control plane can take minutes to converge upon remote failures




Second elapsed between the data plane failure and the control plane learning about it

While the control plane can take minutes to learn about a failure, the actual Internet traffic is affected almost instantaneously


How about we track this signal instead?

# Internet traffic end-points retransmit packets upon experiencing packet drops



## Many end-points retransmitting leads to waves of retransmission

Number of retransmissions



### Tracking this signal in the data plane is challenging

Challenges

Signal is noisy

packets loss are routinely observed

Signal fades away quickly

due to the exponential backoff

Signal is compounded over many small ones

requires per-connection tracking, which is hard to scale

## We solve these challenges by considering a subset of the signal that we carefully craft for maximal signal-to-noise ratio

Solutions

Signal is noisy

Focus on retransmissions caused by bursty losses

Signal fades away quickly


Focus on active flows (fast to retransmit after a failure)

Signal is compounded over many small ones


Rely on scalable data structures and sampling

Blink works well in practice,

with an inference accuracy above 80% in most cases




# Blink works well in practice, with an inference accuracy above 80% in most cases



Failure scenarios


Blink works well in practice,

with an inference speed below 1 second in most cases



### Blink works well in practice,


### with an inference speed below 1 second in most cases





Failure scenarios


What about actuation?

Where do we send the traffic upon detecting a failure?











As for failures, Blink relies on data plane signals to pick a working backup path





# We intend to generalize the signals we track, for a wider variety of applications

reliability reroute around fine-grained failures

performance steer traffic along the most performant path

security detect unwanted traffic redirection

### Part II: Taking control

applications

frameworks

methods

monitoring/inference

### Adaptive Network Monitoring



Alexander Dietmüller




Albert Gran Alcoz



Albert Laurent Vanbever


## We're building an adaptive monitoring framework that can learn high-quality traffic distributions

- computes traffic distribution
   in the control plane, on traffic samples
- scores these distributions
   in the data plane, on *all* traffic
- adapts the sampling rate according to the score



Our framework enables to learn distribution better and faster than simply randomly sampling traffic

Distance from true distribution (Jensen-Shannon)



# Part II: Taking control

applications

frameworks

methods

monitoring/inference

# In-network inference



Coralie Busse-Grawitz Roland Meier Alexander Dietmüller Tobias Bühler Laurent Vanbever









### Why (and How) Networks Should Run Themselves

Nick Feamster and Jennifer Rexford
Princeton University

#### **Abstract**

The proliferation of networked devices, systems, and applications that we depend on every day makes managing networks more important than ever. The increasing security, availability, and performance demands of these applications suggest that these increasingly difficult network management


relationships between them and user quality of experience become increasingly complex. Twenty years ago, we had some hope of (and success in) creating clean, closed-form models of individual protocols, applications, and systems [4, 24]; today, many of these are too complicated for closed-form analysis. Prediction problems such as determining how search query response time would vary in response to the placement

Performing automated, real-time inference: The past ten years has demonstrated significant promise in using machine learning to both detect and predict network attacks; we must build on the increasing amount of work in automated infer-


# Are programmable network devices powerful enough for machine learning inference?

Yep!


# We're building a real-time, in-network inference framework



Optimizing random forest models for programmable network devices



Compiling random forest models to programmable network devices



Performing runtime classification at Tbps

Early, accurate & efficient classification of an ongoing flow as an optimization problem


Given a labeled dataset  $\mathcal{F}$  and a threshold  $\tau$  find a classifier C such that

- $accuracy(C) >= \tau$
- C fits in programmable network devices

### while

- minimizing memory usage
- maximizing classification speed

Our prototype is already able to classify traffic after few packets, with an accuracy which is on-par with software-based solutions



# Part II: Taking control

applications

frameworks

methods

some of our challenges lying ahead Building and operating truly self-driving networks require us to overcome fundamental challenges

data

correctness

interpretability

data

correctness

interpretability

data is network-dependent

poor generalization capabilities

interesting events are rare

few interesting examples (if any)

data can easily be polluted

by anyone with a Internet connection...

how do we...

data

correctness

interpretability

ensure correctness?

network should be reachable

guarantee stability?

agents can clash with each other

reason about optimality?

data-driven > non-data-driven (?)

data

how can operators...

correctness

reason about self-driving networks? especially in partial deployment

interpretability

debug their self-driving networks?
manual override

# Self-driving/monitoring networks

in the age of deep network programmability

operator assistance

2 partial automation

assisting operators

Part I

3 conditional automation

4 high automation

Part II taking control

full automation

too futuristic? 🙂



# Self-driving/monitoring networks

in the age of deep network programmability





Laurent Vanbever

nsg.ee.ethz.ch

TMA

June 19 2019